

**NAME**

update-smart-drivedb - update smartmontools drive database

**SYNOPSIS**

**update-smart-drivedb** [*OPTIONS*] [*DESTFILE*]

**DESCRIPTION**

[This man page is generated for the Linux version of smartmontools. It does not contain info specific to other platforms.]

**update-smart-drivedb** updates `/var/lib/smartmontools/drivedb/drivedb.h` or *DESTFILE* from smartmontools SVN repository.

It tries to download first from the current branch and then from trunk. The tools used for downloading are either [curl\(1\)](#), [wget\(1\)](#), [lynx\(1\)](#), or [svn\(1\)](#).

The old file is kept if the downloaded file is identical (ignoring the differences in Id string) otherwise it is moved to **drivedb.h.old**.

**OPTIONS****-s SMARTCTL**

Use the [smartctl\(8\)](#) executable at path SMARTCTL for drive database syntax check. The form `'-s -'` disables the syntax check. The default is `/usr/sbin/smartctl`.

**-t TOOL**

Use TOOL for download. TOOL is one of: *curl wget lynx svn*. The default is the first one found in PATH.

**-u LOCATION**

Use URL of LOCATION for download. LOCATION is one of:

*sf* (Sourceforge code browser via HTTPS),

*svn* (SVN repository via HTTPS),

*svni* (SVN repository via HTTP),

*trac* (Trac code browser via HTTPS).

The default is *svn*.

**--cacert FILE**

Use CA certificates from FILE to verify the peer.

**--capath DIR**

Use CA certificate files from DIR to verify the peer.

**--insecure**

Don't abort download if certificate verification fails. This option is also required if a HTTP URL is selected with `'-u'` option.

**--dryrun**

Print download commands only.

**-v**

Verbose output.

**EXAMPLES**

```
# update-smart-drivedb
```

```
/var/lib/smartmontools/drivedb/drivedb.h updated from branches/RELEASE_6_6_DRIVEDB
```

**EXIT STATUS**

The exit status is 0 if the database has been successfully updated. If an error occurs the exit status is 1.

**FILES**

**/usr/sbin/update-smart-drivedb**

full path of this script.

**/usr/sbin/smartctl**

used to check syntax of new drive database.

**/var/lib/smartmontools/drivedb/drivedb.h**

current drive database.

**/var/lib/smartmontools/drivedb/drivedb.h.old**

previous drive database.

**/var/lib/smartmontools/drivedb/drivedb.h.error**

new drive database if rejected due to syntax errors.

**/var/lib/smartmontools/drivedb/drivedb.h.lastcheck**

empty file created if downloaded file was identical.

## AUTHORS

**Christian Franke.**

This manual page was originally written by **Hannes von Haugwitz** <[hannes@vonhaugwitz.com](mailto:hannes@vonhaugwitz.com)>.

## REPORTING BUGS

To submit a bug report, create a ticket in smartmontools wiki:

<<http://www.smartmontools.org/>>.

Alternatively send the info to the smartmontools support mailing list:

<<https://lists.sourceforge.net/lists/listinfo/smartmontools-support>>.

## SEE ALSO

[smartctl\(8\)](#), [smartd\(8\)](#).

## PACKAGE VERSION

smartmontools-6.6 2016-05-31 r4324

\$Id: update-smart-drivedb.8.in 4223 2016-02-26 20:18:40Z chrfranke \$